

DURA-LOK FLOORING



TOTAL VALUE. TOTAL SYSTEMS.™

OTHER FLOORING OPTIONS ALSO AVAILABLE



CUT-LOK FLOORING

Designed with a 12% opening that prevents restrictions to airflow, lanced extrusions and deep corrugated ribs across a crowned surface for maximum stability.



COR-LOK FLOORING

Available in 18 & 20 gauge and with a 12% open perforation that prevents restrictions in airflow. Full width corrugation and smooth surface for easy cleaning.

GSI'S NEWEST FLOORING OPTION

GSI's Dura-Lok floor features 3.5" wide sections for a stronger more stable floor. This flooring has a flat top design for a smooth surface, promoting easier sweepability. Two perforation options are available: 0.094" (standard) and 0.050" (small grain).

GSI manufactures many agri-floor designs to meet your grain type or aeration requirements. All plank floors are galvanized for lasting durability and feature a unique locking system for reduced floor movement and solid support.

DURA-LOK FLOOR

DOUBLE PLANK DESIGN

- 3.5" sections for increased strength and stability.
- GSI's strongest flooring.

SMOOTH SURFACE

- Flat-top design makes Dura-Lok floor easier to sweep.

PERFORATION OPTIONS

- Standard: 0.094"
- Small Grain: 0.050"

FLOOR-SUPPORT OPTIONS

- Mono-Rail supports.
- Smooth Top Air Flow (up to 68 ft. eave heights).

AVAILABILITY

- In Bins up to 105 ft. diameter.
- Up to 90 ft. eave heights.



Double Plank Design

Dura-Lok flooring features 3.5" sections for increased strength and stability.



Mono-Rail Supports

Dura-Lok flooring sits on our commercial grade Mono-Rail support system.

www.gsiag.com



TOTAL VALUE. TOTAL SYSTEMS.™

GS-011 AUG/11 Copyright ©2011 by The GSI Group, LLC.
Printed in the USA | Due to continual improvements, The GSI Group, LLC.
reserves the right to change designs and specifications without notice.



GS-011

GSI GROUP

